

0260/001-xx | 1660/001-xx | 0160/001-xx
Polyfin Verbundblech

Product Laminated sheet made of galvanised sheet steel, with synthetic foil lamination on the top and protective coating on the underside.

Intended use

- Suitable as drip edge profile at bracket mounted gutters, roof edge trim sheet, intermediate fastening or valley fastening, etc.
- Very good weldability
- Simple and fast processing

Technical data	Product build up:	Protective coating on underside Galvanised sheet steel, thickness 0.6 mm Topside plastic coating in a thickness of 0.8 mm, in the colours light grey, black or white
	Total thickness:	Approx. 1.4 mm
	Folding angle:	< 315°
	Intermediate angle:	> 45°
	Folding length:	≥ 15 mm

Packaging	POLYFIN laminated metal sheets	Colour top side	Packaging unit	Unit
	1.0 m x 2.0 m			
	0260 / 001-05	light grey	30 sheets / pallet	m ²
	1660 / 001-05	white	30 sheets / pallet	m ²
	0160 / 001-05	black	30 sheets / pallet	m ²
	Weight: approx 12 kg / sheet			
	POLYFIN laminated metal coils	Colour top side	Packaging unit	unit
	length = 30.0 m, width = 1.0 m			
	0260 / 001-11	hellgrau	4 coils / pallet	m ²
	1660 / 001-11	weiß	4 coils / pallet	m ²
	0160 / 001-11	schwarz	4 coils / pallet	m ²
	Weight: approx 180 kg / coil			

The declared data are indices based on the statistical quality control and refer to the date of production. Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method. All specifications are without obligation. The user must assess the suitability of the product for the particular purpose and ensure the user's access to the current version of the product data sheet.

Subject to alteration without notice.

Storage conditions: The products have to be stored in original packaging, being protected from direct sun light, UV-beams and extreme conditions like heat, frost, moisture, etc. During cold season store the products in a frost-free area (+5°C) for 12 hours before application.

Development, Production and Sales of our products according to ISO 9001.