



H 52020
BARUPLAN SUPER KVD EW 55 K

bueho.pdf.product.product_type	Root resistant SBS-modified bitumen membrane with polyester reinforcement for GREEN ROOFS
bueho.pdf.product.up_side	Light surface protection (Slate) with 8 cm selvedge (foil)
bueho.pdf.product.down_side	Foil
bueho.pdf.product.usage	• Root resistant Cap sheet of bituminous GREEN ROOF-systems
bueho.pdf.product.norms	EN 13707
bueho.pdf.product.handling	Torch-on method Side laps min. 8 cm, end laps min. 10 cm overlap
bueho.pdf.product.packaging	bueho.pdf.product.packaging_size

bueho.pdf.product.attribute.description	bueho.pdf.product.attribute.norms	bueho.pdf.product.attribute.unit
Length	EN 1848-1	m
Width	EN 1848-1	m
Straightness	EN 1848-1	mm/10m
Mass per unit area	EN 1849-1	kg/m ²
Thickness	EN 1849-1	mm
Watertightness	EN 1928	bt
External fire exposure	EN 13501-5	Klasse
Reaction to fire test	EN 13501-1	Klasse
Shear resistance of joints	EN 12317-1	N/50mm
Tensile force long./trans.	EN 12311-1	N/50mm
Elongation at single-end breaking force	EN 12311-1	%
Resistance to impact	EN 12691	mm
Resistance to static loading	EN 12730	kg
Resistance to tearing (nail shank) long./trans.	EN 12310-1	N
Dimensional stability	EN 1107-1	%
Flexibility at low temperatures	EN 1109	°C
Flow resistance at elevated temperature	EN 1110	°C
Root resistance	EN 13948	Klasse bt
Flexibility at low temperatures after artificial aging	EN 1109	
Water vapour transmission	EN 1931	μ

[1] according to certified system
bueho.pdf.product.npd