

In accordance to Annex III of Regulation (EU) Nr. 305/2011

Declaration of performance No. Identification code of the product-type

**LE-H94053-02****Büsscher GMS-Noppenbahn 08/2.0****Purpose**

- Waterproofing membrane with moisture barrier and ventilation type V

**Name, contact producer**

BÜSSCHER &amp; HOFFMANN GmbH

A-4470 (AT) Fabrikstraße 2

Tel.: +43 7223 823 23 0

Web: www.bueho.com

E-Mail: office@bueho.at

**Systems of assessment and verification of constancy of performance**

system2+

EN 13967:+A1:2017

**Harmonized standard**

EN 13967:+A1:2017

**Notified body**

0799 KIWA MPA Bautest GmbH, TBU Gutenbergstraße 29 , D-48268 Greven

**Certificate of conformity**

0799-CPR-304

**Declared performance**

| Essential characteristics                            | Performance                         | Harmonized technical specification |
|------------------------------------------------------|-------------------------------------|------------------------------------|
| Reaction to fire test                                | E                                   | EN 13967:+A1:2017                  |
| Watertightness                                       | wasserdicht W1 kn/m <sup>2</sup>    | EN 13967:+A1:2017                  |
| Tensile force long./trans.                           | ≥ 310 / ≥ 260 N/50 mm               | EN 13967:+A1:2017                  |
| Resistance to static loading                         | keine Perforation<br>bei 20 kg/24 h | EN 13967:+A1:2017                  |
| Resistance to impact                                 | ≥ 450 mm                            | EN 13967:+A1:2017                  |
| Shear resistance of joints                           | NPD                                 | EN 13967:+A1:2017                  |
| Durability of waterproofness to artificial aging     | wasserdicht                         | EN 13967:+A1:2017                  |
| Durability of waterproofness to artificial chemicals | wasserdicht                         | EN 13967:+A1:2017                  |
| Resistance to tearing (nail shank)                   | ≥ 215 / ≥ 225 N                     | EN 13967:+A1:2017                  |
| Hazardous substances                                 | NPD                                 | EN 13967:+A1:2017                  |

The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by



**Bmstr. Dipl. Ing. Karl Landl**  
**General Manager**

[a] This declaration of performance is available in copy at the website of the producer

[b] Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method.