In accordance to Annex III of Regulation (EU) Nr. 305/2011



LE-H51256-04 B

Büsscher PeriSeal 4,5

Purpose

- Blindside waterproofing systems
- · Basement waterproofing systems against soil moisture and water

Name, contact producer

BÜSSCHER & HOFFMANN GmbH A-4470 (AT) Fabrikstraße 2 Tel.: +43 7223 823 23 0

Web: www.bueho.com E-Mail: office@bueho.at

Systems of assessment and verification of constancy of performance

system2+	EN 13969:2004 + A1:2006
Harmonized standard	EN 13969:2004 + A1:2006

Declared performance

		Harmonized technical
Essential characteristics	Performance	specification
Watertightness	400 kPa	EN 13969:2004 + A1:2006
Reaction to fire test	Е	EN 13969:2004 + A1:2006
Shear resistance of joints	NPD	EN 13969:2004 + A1:2006
Tensile force long./trans.	1000/800 (±250/±250)	EN 13969:2004 + A1:2006
	N/50mm	
Elongation at single-end breaking force	45/50 (±10/±10) %	EN 13969:2004 + A1:2006
Resistance to impact	1000 mm	EN 13969:2004 + A1:2006
Resistance to static loading	15 kg	EN 13969:2004 + A1:2006
Resistance to tearing (nail shank) long./trans.	200/200 (±50/±50) N	EN 13969:2004 + A1:2006
Flexibility at low temperatures	-20 °C	EN 13969:2004 + A1:2006
Watertightness transmission after artifical aging	400 kPa	EN 13969:2004 + A1:2006
Watertightness after exposure to liquid chemicals	NPD	EN 13969:2004 + A1:2006
Hazardous substances	Keine	EN 13969:2004 + A1:2006

The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by

Vaul Louds

Bmstr. Dipl. Ing. Karl Landl

General Manager

Issue date: 04.10.2024 Page 1 / 1

[[]a] This declaration of performance is available in copy at the website of the producer

[[]b] Consider state of the art, standards, legal provisions and guidelines for the suitability of the mentioned field of application and application method.